


SpringLamp® Compact Fluorescent G10-20 Globes

NPF

Applications:

Perfect for many incandescent applications.

- + Decorative Fixtures
- + Wall Sconces




Special Applications Options (Ordering Suffix):


- 3100°K (31K), 3500°K (35K), 4100°K (41K), 5100°K (51K)
- Shatter Resistant (SS) R20 only

Features and Benefits


- Long life CFL, 8,000 hours average rated life
- Amalgam technology - provides cooler operating temperatures for consistent performance in any position
- No lead glass- Better lumen maintenance over life of bulb
- 2700°K color temperature closest to incandescent light
- Medium and Candelabra base
- Replace less often, ideal for hard to reach places
- U.L. Listed for wet locations - use indoors or outdoors
- 12 Month Warranty
- Quickstart technology - fast run up time



1G2002 / 1G2004



1G2002C / 1G2004C



1G1002



1G1002C

Catalog Number

Notes

Type



Specifications

End of Life Protection.....	Yes
Ballast Type	Electronic
Starting Method.....	Modified Rapid Start
Input Line Voltage	120VAC
Input Line Frequency	50/60HZ
Lamp Life (rated)	8,000 Hours
Color Temperature	2700°K
Color Rendering Index	82
Minimum Starting Temperature	-20 ° F
Maximum Operating Temperature	160 ° F
U.L. / C.U.L. Listed	Yes
FCC Compliance	Part 18, Subpart C
Lamp Operating Frequency	45 KHZ
Lamp Current Crest Factor	< 1.60
Maximum Open Circuit Voltage	600V
Power Factor	> .50
Total Harmonic Distortion	< 150%

Special Application Notes

- UL approved for wet location in Base Up position only. Base Up position is defined as screw base in a 12:00 position. Any other base position must be in a UL approved weatherproof fixture.

Warranties and Certifications:	Item#	Wattage	Incandescent Wattage Comparison	Initial Lumens	Input Line Current	M.O.L. (inches)	Diameter (inches)	Life vs. Incandescent	Base Type
 12 MONTH WARRANTY TCP reserves the right to void the warranty for any mis-application of these products.	1G1002	2	10	80	.03A	3.0	1.5	5x	Medium
	1G1002C	2	10	80	.03A	3.0	1.5	5x	Candelabra
	1G2002	2	15	170	.03A	3.4	2.5	5x	Medium
	1G2002C	2	15	170	.03A	3.2	2.5	5x	Candelabra
	1G2004	4	25	200	.07A	3.4	2.5	5x	Medium
	1G2004C	4	25	200	.07A	3.2	2.5	5x	Candelabra