



**New**

# Allusion™ LED lamps with smooth warm dimming

**ENERGY EFFICIENT • MULTIPLE OPTIONS • 25,000 HOURS**

Introducing TCP® latest offering of Allusion LED lamps—the “incandescent-like” LEDs that offer a unique dimming profile, replicating true incandescent/halogen dimming.

### LIMITLESS OPTIONS FOR THE FOLLOWING APPLICATIONS

- Table Lamps
- Sconces
- Chandeliers
- Track Lights
- Floor Lamps
- Ceiling Fixtures
- Decorative
- Recessed Downlights

| FEATURES  | BENEFITS   |
|---|--|
| Up to 85% more efficient than incandescent/halogen replacements | Instant energy savings   |
| Long life: 25,000 hours/<br>30,000 hours (SL16)                 | Minimizes replacement and maintenance costs  |
| Smooth warm dimming   | Creates the perfect atmosphere   |
| UL approved for damp location*                                  | Can be used outdoors when protected from elements—withstands humidity indoors/outdoors |
| Shatter resistant   | Lower risk of injury and breakage  |

### SPECIFICATIONS

Color Temperatures..... 3000K to 2000K/3000K to 1800K (MR16)  
 Input Line Voltage ..... 120 VAC/12 VAC (MR16)  
 Input Line Frequency..... 50/60HZ  
 Lamp Life (Rated) ..... 25,000 hours/30,000 hours (SL16)  
 Minimum Starting Temp ..... -22F/-30C  
 Maximum Operating Temp..... 40°C  
 CRI..... 80



**3 YEAR WARRANTY**  
MR16 lamps



**5 YEAR WARRANTY**  
All other lamps



\* PAR38, PAR30 and PAR20 lamps UL approved for wet location



PAR38  
40°/25°  
Beam Angles



PAR30  
40°/25°  
Beam Angles



PAR20  
40°/25°  
Beam Angles



MR16 GU5.3  
40°/20°  
Beam Angles



SL16  
STARLIGHT  
110° Beam Angle

we know light.™



**New** Allusion™ LED Lamps  
with smooth warm dimming

**ENERGY EFFICIENT • MULTIPLE OPTIONS • 25,000 HOURS**

| ITEM # | DESCRIPTION | VOLTAGE | LED WATTS | WATTAGE EQUIVALENT | LUMENS | LPW | CCT | COLOR TEMPERATURE | BEAM ANGLE | MOL (inches) | DIA (inches) | BASE |
|--------|-------------|---------|-----------|--------------------|--------|-----|-----|-------------------|------------|--------------|--------------|------|
|--------|-------------|---------|-----------|--------------------|--------|-----|-----|-------------------|------------|--------------|--------------|------|

**LED PAR38 90W Equivalent**

**15W LED • 25,000 hours**



|             |                                |      |      |    |     |       |     |                |     |     |      |     |
|-------------|--------------------------------|------|------|----|-----|-------|-----|----------------|-----|-----|------|-----|
| L15P38DNFLA | LED 15W PAR38 30K Allusion NFL | 120V | 12.5 | 90 | 975 | 78.00 | >80 | 3000K to 2000K | 25° | 5.4 | 4.75 | E26 |
| L15P38DFLA  | LED 15W PAR38 30K Allusion FL  | 120V | 12.5 | 90 | 975 | 78.00 | >80 | 3000K to 2000K | 40° | 5.4 | 4.75 | E26 |

**LED PAR30 90W Equivalent**

**15W LED • 25,000 hours**



|             |                                |      |      |    |     |       |     |                |     |     |     |     |
|-------------|--------------------------------|------|------|----|-----|-------|-----|----------------|-----|-----|-----|-----|
| L15P30DNFLA | LED 15W PAR30 30K Allusion NFL | 120V | 12.5 | 90 | 950 | 76.00 | >80 | 3000K to 2000K | 25° | 4.7 | 3.8 | E26 |
| L15P30DFLA  | LED 15W PAR30 30K Allusion FL  | 120V | 12.5 | 90 | 950 | 76.00 | >80 | 3000K to 2000K | 40° | 4.7 | 3.8 | E26 |

**LED PAR20 50W Equivalent**

**7W LED • 25,000 hours**



|            |                               |      |     |    |     |       |     |                |     |     |     |     |
|------------|-------------------------------|------|-----|----|-----|-------|-----|----------------|-----|-----|-----|-----|
| L7P20DNFLA | LED 7W PAR20 30K Allusion NFL | 120V | 6.5 | 50 | 525 | 80.77 | >80 | 3000K to 2000K | 25° | 3.4 | 2.5 | E26 |
| L7P20DFLA  | LED 7W PAR20 30K Allusion FL  | 120V | 6.5 | 50 | 525 | 80.77 | >80 | 3000K to 2000K | 40° | 3.4 | 2.5 | E26 |

**LED MR16 50W Equivalent**

**7W LED • 25,000 hours**



|                |                              |     |   |    |     |       |     |                |     |     |     |     |
|----------------|------------------------------|-----|---|----|-----|-------|-----|----------------|-----|-----|-----|-----|
| L712VMR16DNFLA | LED 7W MR16 30K Allusion NFL | 12V | 6 | 50 | 350 | 58.33 | >80 | 3000K to 1800K | 20° | 1.9 | 2.0 | 5.3 |
|----------------|------------------------------|-----|---|----|-----|-------|-----|----------------|-----|-----|-----|-----|

**LED SL16 Starlight**

**13W LED • 30,000 hours**



|             |                           |      |    |   |      |       |     |                |      |     |     |     |
|-------------|---------------------------|------|----|---|------|-------|-----|----------------|------|-----|-----|-----|
| L15SL16D30A | LED 13W SL16 30K Allusion | 120V | 13 | — | 1200 | 92.30 | >80 | 3000K to 2000K | 110° | 3.8 | 6.3 | E26 |
|-------------|---------------------------|------|----|---|------|-------|-----|----------------|------|-----|-----|-----|



**RoHS**  
COMPLIANT

**3 YEAR**  
WARRANTY  
MR16 lamps

**5 YEAR**  
WARRANTY  
All other lamps

**Allusion™**

For the most up-to-date specs, please visit [www.tcpi.com](http://www.tcpi.com)

TCP®

325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | [tcpi.com](http://tcpi.com)

©TCP JUN 2019/WF142005rev