



we know light.™

# Starlight LED lamps

**ENERGY SAVINGS • 30,000 HOURS • 5 YEAR WARRANTY**

Shine as bright as a star with our new LED Starlight series. The sleek, modern shape can be used in a wide variety of applications—from pendants to sockets and everywhere in between.

## LIMITLESS OPTIONS FOR THE FOLLOWING APPLICATIONS

- Commercial
- Industrial
- Retail
- Residential

FEATURES	BENEFITS
Up to 85% more efficient than incandescent/halogen replacements	Instant energy savings
Long life: 30,000 hours	Minimizes replacement and maintenance costs
Smooth warm dimming	Creates the perfect atmosphere
UL approved for damp location	Can be used outdoors when protected from elements—withstands humidity indoors/outdoors
Sleek, low profile design	Unique shape for limitless applications

## SPECIFICATIONS

Color Temperatures .....	3000K; 4000K; 5000K;
.....	3000K to 1800K
Input Line Voltage .....	120V
Input Line Frequency .....	50/60HZ
Lamp Life (Rated) .....	30,000 hours
Minimum Starting Temp .....	-22F/-30C
Maximum Operating Temp .....	45°C
CRI .....	80



**5 YEAR WARRANTY**  
\* Based on 12 hours use per day

**RoHS COMPLIANT**



SL13



SL16



SL19



SL22



# Starlight Lamps

**ENERGY SAVING • 30,000 HOURS • 5 YEAR WARRANTY**

ITEM #	DESCRIPTION	VOLTAGE	LED WATTS	WATTAGE EQUIVALENT	LUMENS	LPW	CRI	COLOR TEMP	BEAM ANGLE	MOL (inches)	DIA (inches)	BASE
--------	-------------	---------	-----------	--------------------	--------	-----	-----	------------	------------	--------------	--------------	------

## LED SL13 Starlight 65W Equivalent

### 9W LED • 30,000 hours

L9SL13D3030K	LED STARLIGHT DIM 9W 30K	120V	9	65	950	105.56	80	3000K	110°	3.8	5.2	E26
L9SL13D3040K	LED STARLIGHT DIM 9W 40K	120V	9	65	1000	111.11	80	4000K	110°	3.8	5.2	E26
L9SL13D3050K	LED STARLIGHT DIM 9W 50K	120V	9	65	1000	111.11	80	5000K	110°	3.8	5.2	E26

## LED SL16 Starlight 100W Equivalent

### 15W LED • 30,000 hours

L15SL16D3030K	LED STARLIGHT DIM 15W 30K	120V	15	100	1625	108.33	80	3000K	110°	3.8	6.3	E26
L15SL16D3040K	LED STARLIGHT DIM 15W 40K	120V	15	100	1700	113.33	80	4000K	110°	3.8	6.3	E26
L15SL16D3050K	LED STARLIGHT DIM 15W 50K	120V	15	100	1750	116.67	80	5000K	110°	3.8	6.3	E26
L15SL16D30A	LED ALLUSION 15W WARM-DIMMING	120V	15	100	1750	116.67	80	3000K to 1800K	110°	3.8	6.3	E26

## LED SL19 Starlight 140W Equivalent

### 19W LED • 30,000 hours

L19SL19D3030K	LED STARLIGHT DIM 19W 30K	120V	19	140	2100	110.53	80	3000K	110°	4.5	7.75	E26
L19SL19D3040K	LED STARLIGHT DIM 19W 40K	120V	19	140	2250	118.42	80	4000K	110°	4.5	7.75	E26
L19SL19D3050K	LED STARLIGHT DIM 19W 50K	120V	19	140	2250	118.42	80	5000K	110°	4.5	7.75	E26

## LED SL22 Starlight 160W Equivalent

### 22W LED • 30,000 hours

L22SL22D3030K	LED STARLIGHT DIM 22W 30K	120V	22	160	2350	106.82	80	3000K	110°	4.8	8.9	E26
L22SL22D3040K	LED STARLIGHT DIM 22W 40K	120V	22	160	2450	111.36	80	4000K	110°	4.8	8.9	E26
L22SL22D3050K	LED STARLIGHT DIM 22W 50K	120V	22	160	2450	111.36	80	5000K	110°	4.8	8.9	E26

## LED SL122 Starlight 200W Equivalent

### 25W LED • 30,000 hours

L25SL22HD3030K	LED STARLIGHT DIM 25W 30K HL	120V	25	200	3100	124.00	80	3000K	110°	4.8	8.9	E26
----------------	------------------------------	------	----	-----	------	--------	----	-------	------	-----	-----	-----

Black, silver and custom colors are available by special order.



**RoHS**  
COMPLIANT

**5** YEAR  
WARRANTY

\*Based on 12 hours use per day

For the most up-to-date specs, please visit [www.tcp.com](http://www.tcp.com)

TCP®

325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | [tcp.com](http://tcp.com)

©TCP FEB 2019/WF143350