



Starlight LED Lamps

Product Specifications



Shine as bright as a star with our new LED Starlight series. The sleek, modern shape can be used in a wide variety of applications—from pendants to sockets and everywhere in between.

Reasons to choose the Starlight LED Lamp from TCP

- Sleek, low profile design provides a unique shape for limitless applications
- Smooth warm dimming creates the perfect atmosphere
- Up to 85% more efficient than incandescent/halogen replacements
- Long, 30,000 hours life minimizes replacement and maintenance costs
- UL approved for damp locations means the lamp can be used outdoors when protected from the elements

Ideal Applications

- Commercial
- Industrial
- Retail
- Residential

Specifications:

Color Temperatures.....	3000K; 4000K; 5000K;	Lamp Life (Rated)	30,000 hours
.....	3000K to 1800K	Minimum Starting Temp	-22F/-30C
Input Line Voltage	120V	Maximum Operating Temp.....	45°C
Input Line Frequency.....	50/60HZ	CRI.....	80

Specifications:



SL13



SL16



SL19



SL22

ITEM #	DESCRIPTION	VOLTAGE	LED WATTS	WATTAGE EQUIVALENT	LUMENS	LPW	CRI	COLOR TEMP	BEAM ANGLE	MOL (inches)	DIA (inches)	BASE
LED SL13 Starlight 65W Equivalent – 9W LED • 30,000 hours												
L9SL13D3030K	LED STARLIGHT DIM 9W 30K	120V	9	65	950	105.56	80	3000K	110°	3.8	5.2	E26
L9SL13D3040K	LED STARLIGHT DIM 9W 40K	120V	9	65	1000	111.11	80	4000K	110°	3.8	5.2	E26
L9SL13D3050K	LED STARLIGHT DIM 9W 50K	120V	9	65	1000	111.11	80	5000K	110°	3.8	5.2	E26
LED SL16 Starlight 100W Equivalent – 15W LED • 30,000 hours												
L15SL16D3030K	LED STARLIGHT DIM 15W 30K	120V	15	100	1625	108.33	80	3000K	110°	3.8	6.3	E26
L15SL16D3040K	LED STARLIGHT DIM 15W 40K	120V	15	100	1700	113.33	80	4000K	110°	3.8	6.3	E26
L15SL16D3050K	LED STARLIGHT DIM 15W 50K	120V	15	100	1750	116.67	80	5000K	110°	3.8	6.3	E26
L15SL16D30A	LED ALLUSION 15W WARM-DIMMING	120V	13	100	1200	116.67	80	3000K to 2000K	110°	3.8	6.3	E26
LED SL19 Starlight 140W Equivalent – 19W LED • 30,000 hours												
L19SL19D3030K	LED STARLIGHT DIM 19W 30K	120V	19	140	2100	110.53	80	3000K	110°	4.5	7.75	E26
L19SL19D3040K	LED STARLIGHT DIM 19W 40K	120V	19	140	2250	118.42	80	4000K	110°	4.5	7.75	E26
L19SL19D3050K	LED STARLIGHT DIM 19W 50K	120V	19	140	2250	118.42	80	5000K	110°	4.5	7.75	E26
LED SL22 Starlight 160W Equivalent – 22W LED • 30,000 hours												
L22SL22D3030K	LED STARLIGHT DIM 22W 30K	120V	22	160	2350	106.82	80	3000K	110°	4.8	8.9	E26
L22SL22D3040K	LED STARLIGHT DIM 22W 40K	120V	22	160	2450	111.36	80	4000K	110°	4.8	8.9	E26
L22SL22D3050K	LED STARLIGHT DIM 22W 50K	120V	22	160	2450	111.36	80	5000K	110°	4.8	8.9	E26
LED SL122 Starlight 200W Equivalent – 25W LED • 30,000 hours												
L25SL22HD3030K	LED STARLIGHT DIM 25W 30K HL	120V	25	200	3100	124.00	80	3000K	110°	4.8	8.9	E26

Matching Pendant Mount is also available:

- 6' adjustable length mounts directly to junction box
- 555PMWHT Pendant Mount White

