

Specifications:

Operating voltage	120-277Vac, 50/60Hz
Input Voltage	120-230-277-347VAC
Operational Frequencies	50/60 Hz
Rated load	800VA @ 120VAC Ballast 1200VA @ 277VAC Ballast
Standby Power Consumption	120V – 130mW – .13W 277V – 450mW – .45W
Time Delay	30 seconds – 20 minutes (factory set to 30 sec – no power required to set)
Detection zone	Max.(D x H): 16m x 15m
Mounting height	15m Max.
Motion detection	0.5-3m/s
Operating temperature.....	-20°C - 60°C
IP rating	IP20
Operating Temperature Range....	14-160° F (-10-71° C)
Cold Storage Operating Temperature Range	-40-160° F (-40-71° C)
Storage Temperature Range	-14-160° F (-25-71° C)
Relative Humidity	20-90% non-condensing
Color	White
Warranty	5 year limited warranty



Listing

RoHS Compliant

Warranty

Five year limited warranty against defects in manufacturing

Ordering Matrix

Item #	DESCRIPTION
LS1	PIR Fixture Mount High Bay Sensor
LS1D	PIR Fixture Mount High Bay Sensor with Daylight Harvest and Bi-level Dimming Functionality

For the most up-to-date specs and warranty information, please visit www.tcpi.com

Specifications and dimensions subject to change without notice.