

Specifications:

Operating Voltage	Dual 120/277V
Battery	3.6V Long life, maintenance-free, rechargeable NiCd battery
Battery Backup Function	Internal solid-state transfer switch automatically connects the internal battery to LED board and LED lamp heads for minimum 90-minute emergency illumination
Battery Recharge	Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours
Illumination	0.5 watt LED per lamp head
Lamp Heads	Adjustable long lasting, efficient ultra bright white LED lamp heads
Mounting	EZ-snap mounting canopy included for top or end mount. Universal knockout pattern on back plate for wall mount
Housing	Injection-molded, engineering grade, 5VA flame retardant, high-impact resistant, thermoplastic in white finish
Warranty	One year warranty on all electronics and housing. Battery prorated for one year
Operating Temperature	UL Listed for damp locations (0°C – 40°C)
CEC	Certified to CEC under Title 20 Regulations
Color	Available with white housing and choice of red or green lettering




Listing

Meets CEC under Title 20 Regulations, UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.

Warranty

One year limited warranty against defects in manufacturing

Dimensions:



Ordering Information

Item #	DESCRIPTION
LED20786	Low Profile LED Combo Emergency Exit Sign White Housing w/ Red Lettering
LED20787	Low Profile LED Combo Emergency Exit Sign White Housing w/ Green Lettering

Specifications and dimensions subject to change without notice.