



LED Traditional Selectable Recessed Downlight

Specifications:



6 inch Dimmable Downlight



4 inch Dimmable Downlight



ITEM #	DESCRIPTION	VOLTAGE	WATTS	INCANDES. WATTS	LPW	LUMENS	COLOR	CRI	MOL (inches)	DIA (inches)	BEAM ANGLE	BASE	WARRANTY YEARS
LED 75W Equivalent Options													
DR4 Downlight • Dimmable • 35,000 Hour													
L75DR4DCCT1	4" LED Color Selectable Traditional Downlight 2400/2700/3000	120V	10	75	76.5/85/85	765/850/850	2400K/2700K/3000K	80	3.0	5	120°	E26	5
L75DR4DCCT2	4" LED Color Selectable Traditional Downlight 3000/4000/5000	120V	10	75	90/96/91.5	900/960/915	3000K/4000K/5000K	80	3.0	5	120°	E26	5
LED 120W Equivalent Options													
DR56 Downlight • Dimmable • 35,000 Hour													
L120DR56CCT1	5 5/8" LED Color & Wattage Selectable Traditional Beveled Downlight 2400/2700/3000	120V	8/10.5/14.5	120	8W: 95.6/106.3/106.3 10.5W: 95.2/104.8/104.8 14.5W: 86.9/96.6/96.6	8W: 765/850/850 10.5W: 1000/1100/1100 14.5W: 1260/1400/1400	2400K/2700K/3000K	80	3.0	7.4	120°	E26	5
L120DR56DCCT2	5 5/8" LED Color & Wattage Selectable Traditional Beveled Downlight 3000/4000/5000	120V	8/10.5/14.5	120	8W: 113.8/118.1/115 10.5W: 104.8/110.5/106.7 14.5W: 100/95.5/102.3	8W: 910/945/920 10.5W: 1100/1160/1120 14.5W: 1450/1370/1490	3000K/4000K/5000K	80	3.0	7.4	120°	E26	5



TECHNOLOGY CAST IN A BEAUTIFUL LIGHT

For over 20 years, TCP has been designing, developing and delivering energy-efficient lighting into the market. Thanks to our cutting-edge technology and manufacturing expertise, we have shipped billions of high quality lighting products. With TCP, you can count on a lighting product that is designed to meet the needs of the market - that transforms your surroundings and envelopes you in warmth - lighting that generates beauty with every flip of the switch.

Sales:

Date:

Model:

Project:

Rep:

Catalog Number:

Type:

Notes:



For more information on the quality and care TCP can deliver, call us at **800.324.1496** or visit tcp.com

325 Campus Dr. | Aurora, Ohio 44202 | P: 800.324.1496 | F: 877.487.0516