



LED Recessed Flat Face Snap-In CCT Selectable Downlights



TCP's LED Recessed Flat Face Snap-In CCT Selectable Downlights are the perfect choice for remodeling or new construction projects. The slim, energy-efficient design is easy to install and offers a rated lifetime of 50,000 hours.

Reasons to choose the LED Recessed Flat Face Snap-In CCT Selectable Downlights from TCP

- Selectable CCT (27K/30K/35K) or (30K/40K/50K)
- Direct wire - no recessed can required
- Integrated junction box on 4" and 6" models
- 4", 6", and 8" diameter sizes
- Easy installation
- Dimmable
- Slim, low-profile design
- Excellent color consistency
- 50,000 hours rated life
- UL approved for damp locations
- IC rated
- Energy Star® Certified

Ideal Applications

- Retrofits
- New construction
- Residential
- Office
- Retail
- Hospitality
- Drop ceilings
- Remodeling

Applications

Ideal for dimmable 4", 6" and 8" retrofit or new construction downlight applications.

Construction

- Integrated junction box for direct wire application (4" and 6" models)
- 8" models have external junction box
- Spring loaded tabs for easy installation

Electrical

- UL approved for damp locations
- Easily access wiring for quick installation
- 50,000 hours rated life

Optics

- Excellent color consistency
- Smooth, uniform dimming
- Highly-efficient LEDs and driver
- Triac dimming



Listings

cULus Listed, RoHS and Energy Star® Certified

Warranty

Five year limited warranty against defects in manufacturing.

LED Recessed Flat Face Snap-In CCT Selectable Downlights

ITEM #	DESCRIPTION	VOLTAGE	INCAND. WATTS	WATTAGE	LUMENS	LPW	CCT SELECTABLE	CRI	BEAM ANGLE	DIMMABLE	MOL (IN)	DIAMETER (IN)
DR4BLCCT1	4" SNAP-IN CCT 27/30/35	120	75	10	850	85	27K/30K/35K	80	90°	YES	3	5
DR4BLCCT2	4" SNAP-IN CCT 30/40/50	120	75	10	850	85	30K/40K/50K	80	90°	YES	3	5
DR6BLCCT1	6" SNAP-IN CCT 27/30/35	120	85	14	1100	78.6	27K/30K/35K	80	100°	YES	3	7.125
DR6BLCCT2	6" SNAP-IN CCT 30/40/50	120	85	14	1100	78.6	30K/40K/50K	80	100°	YES	3	7.125
DR8CCT1	8" SNAP-IN CCT 27/30/35	120	120	18	1400	77.8	27K/30K/35K	80	110°	YES	1.5	8.75
DR8CCT2	8" SNAP-IN CCT 30/40/50	120	120	18	1400	77.8	30K/40K/50K	80	110°	YES	1.5	8.75

TCP Standard LED Lamps, LED Filament Lamps and TCP Downlights have been tested to work with the following dimmers:

BRAND	MODEL
LUTRON	AYCL-153P
	CTCL-153PD-H
	CTCL-53PD-H
	DV-600P
	DV-600PR-WH
	DV-603PH-WH
	DVCL-153P
	LGCL-153P
	MACL_153M
	MSCL-OP153M
	PD-6WCL
	SCL-153PR
	SELV-300P
	TGCL-153P
MRF2S-6ELV120-WH	
LEVITON	6811
	6602
	6631
	6672
	6672-L
	6674
	DSLO6
	IPL06
COOPER	DAL06P
	SAL06P

*Dimming compatibility tests are performed under a controlled lab environment. Field conditions may vary from this type of environment. Dimmers may differ by age and versions under the same item number which may affect compatibility. Compatibility may also extend beyond this list as TCP products should work with most C-L Type Triac Dimmers. TCP recommends trying a few dimmer-lamp combinations in an on-site test to ensure compatibility and performance before a major installation. If there's a dimmer not on this list we can perform a lab test for compatibility.

TECHNOLOGY CAST IN A BEAUTIFUL LIGHT

For over 20 years, TCP has been designing, developing and delivering energy-efficient lighting into the market. Thanks to our cutting-edge technology and manufacturing expertise, we have shipped billions of high quality lighting products. With TCP, you can count on a lighting product that is designed to meet the needs of the market - that transforms your surroundings and envelopes you in warmth - lighting that generates beauty with every flip of the switch.

Sales:

Date:

Model:

Project:

Rep:

Catalog Number:

Type:

Notes:



For more information on the quality and care TCP can deliver, call us at **800.324.1496** or visit tcp.com

325 Campus Dr. | Aurora, Ohio 44202 | P: 800.324.1496 | F: 877.487.0516