



LED COB PAR Lamps

Product Specifications



TCP's award winning PAR lamps combine traditional beauty with top-notch technology. With the wide variety of options available, you can be sure to find the PAR lamp to meet your needs.

Reasons to choose the LED COB PAR Lamps from TCP

- Provides designer grade light quality with same look as halogen replacements
- Perfect for sensitive display lighting such as galleries
- Enhances colors of focal point while maintaining uniformity throughout the lighting installation
- Track or downlight installations are not strained by excess weight
- Suitable for wet locations—when exposed to water, use only with device base up
- Seamlessly blends into lighting applications

Ideal Applications

- Retail
- Display lights
- Track lighting
- Outdoor settings
- Galleries

Specifications:

Voltage 120V
 Input Line Frequency 50/60HZ
 Lamp Life (Rated) 25,000 hours
 Minimum Starting Temp -7.6°F/-22°C
 Maximum Operating Temp 113°F/ 45°C

CRI ≥ 80
 Beam Angle 15°, 25°, 40°, 60°
 Base E26
 Warranty 5 Years
 Suitable for use in totally enclosed fixtures

Specifications:



ITEM #	DESCRIPTION	WATTS	REPLACEMENT WATTS	LUMENS	LPW	COLOR	CRI	MOL (inches)	DIA (inches)	MEASURED CBCP	BEAM ANGLE
7W P20 Lamps – Dimmable • 25,000 Hours – PHASING OUT for L7P20D25 series, See new PAR20 spec sheet.											
LED8P20D24KFL	LED 7W P20 DIM 24KFL	7	50	550	78.6	2400K	80	3.5"	2.5"	—	40°
LED8P20D24KNFL	LED 7W P20 DIM 24KNFL	7	50	550	78.6	2400K	80	3.5"	2.5"	—	25°
LED8P20D27KFL	LED 7W P20 DIM 27KFL	7	50	600	85.7	2700K	80	3.5"	2.5"	1208	40°
LED8P20D27KFLB	LED 7W P20 DIM 27KFL BLACK	7	50	600	85.7	2700K	80	3.5"	2.5"	1208	40°
LED8P20D27KNFL	LED 7W P20 DIM 27KNFL	7	50	600	85.7	2700K	80	3.5"	2.5"	2030	25°
LED8P20D27KNFL	LED 7W P20 DIM 27KNFL BLACK	7	50	600	85.7	2700K	80	3.5"	2.5"	2030	25°
LED8P20D27KSP	LED 7W P20 DIM 27KSP	7	50	600	85.7	2700K	80	3.5"	2.5"	4898	15°
LED8P20D30KFL	LED 7W P20 DIM 30KFL	7	50	625	89.3	3000K	80	3.5"	2.5"	1187	40°
LED8P20D30KFLB	LED 7W P20 DIM 30KFL BLACK	7	50	625	89.3	3000K	80	3.5"	2.5"	1187	40°
LED8P20D30KNFL	LED 7W P20 DIM 30KNFL	7	50	625	89.3	3000K	80	3.5"	2.5"	2050	25°
LED8P20D30KNFLB	LED 7W P20 DIM 30KNFL BLACK	7	50	625	89.3	3000K	80	3.5"	2.5"	2050	25°
LED8P20D30KSP	LED 7W P20 DIM 30KSP	7	50	625	89.3	3000K	80	3.5"	2.5"	5391	15°
LED8P20D35KFL	LED 7W P20 DIM 35KFL	7	50	675	96.4	3500K	80	3.5"	2.5"	1722	40°
LED8P20D35KNFL	LED 7W P20 DIM 35KNFL	7	50	675	96.4	3500K	80	3.5"	2.5"	4807	25°
LED8P20D41KFL	LED 7W P20 DIM 41KFL	7	50	675	96.4	4100K	80	3.5"	2.5"	1383	40°
LED8P20D41KFLB	LED 7W P20 DIM 41KFL BLACK	7	50	675	96.4	4100K	80	3.5"	2.5"	1383	40°
LED8P20D41KNFL	LED 7W P20 DIM 41KNFL	7	50	675	96.4	4100K	80	3.5"	2.5"	2174	25°
LED8P20D41KNFLB	LED 7W P20 DIM 41KNFL BLACK	7	50	675	96.4	4100K	80	3.5"	2.5"	2174	25°
LED8P20D41KSP	LED 7W P20 DIM 41KSP	7	50	675	96.4	4100K	80	3.5"	2.5"	5411	15°
LED8P20D50KFL	LED 7W P20 DIM 50KFL	7	50	700	100	5000K	80	3.5"	2.5"	1330	40°
LED8P20D50KFLB	LED 7W P20 DIM 50KFL BLACK	7	50	700	100	5000K	80	3.5"	2.5"	1330	40°
LED8P20D50KNFL	LED 7W P20 DIM 50KNFL	7	50	700	100	5000K	80	3.5"	2.5"	2172	25°
LED8P20D50KSP	LED 7W P20 DIM 50KSP	7	50	700	100	5000K	80	3.5"	2.5"	5599	15°

10W P30 Short Neck Lamps – Dimmable • 25,000 Hours

LED12P30SD24KFL	LED 10W P30SN DIM 24KFL	10	75	800	90.0	2400K	80	3.6"	3.8"	1619	40°
LED12P30SD24KNFL	LED 10W P30SN DIM 24KNFL	10	75	800	90.0	2400K	80	3.6"	3.8"	—	25°
LED12P30SD24KSP	LED 10W P30SN DIM 24KSP	10	75	800	85.0	2400K	80	3.6"	3.8"	—	15°
LED12P30SD27KFL	LED 10W P30SN DIM 27KFL	10	75	850	85.0	2700K	80	3.6"	3.8"	1817	40°
LED12P30SD27KFLB	LED 10W P30SN DIM 27KFL BLACK	10	75	850	85.0	2700K	80	3.6"	3.8"	1817	40°
LED12P30SD27KNFL	LED 10W P30SN DIM 27KNFL	10	75	850	85.0	2700K	80	3.6"	3.8"	4025	25°
LED12P30SD27KNFLB	LED 10W P30SN DIM 27KNFL BLACK	10	75	850	85.0	2700K	80	3.6"	3.8"	4025	25°
LED12P30SD27KSP	LED 10W P30SN DIM 27KSP	10	75	850	85.0	2700K	80	3.6"	3.8"	8042	15°
LED12P30SD30KFL	LED 10W P30SN DIM 30KFL	10	75	850	85.0	3000K	80	3.6"	3.8"	1858	40°
LED12P30SD30KFLB	LED 10W P30SN DIM 30KFL BLACK	10	75	850	85.0	3000K	80	3.6"	3.8"	1858	40°

NOTE: All items come in shipping cartons of 12.



LED COB PAR Lamps

ITEM #	DESCRIPTION	WATTS	REPLACEMENT WATTS	LUMENS	LPW	COLOR	CRI	MOL (inches)	DIA (inches)	MEASURED CBCP	BEAM ANGLE
10W P30 Short Neck Lamps – Dimmable • 25,000 Hours - Continued											
LED12P30SD30KNFL	LED 10W P30SN DIM 30KNFL	10	75	850	85.0	3000K	80	3.6"	3.8"	4968	25°
LED12P30SD30KNFLB	LED 10W P30SN DIM 30KNFL BLACK	10	75	850	85.0	3000K	80	3.6"	3.8"	4968	25°
LED12P30SD30KSP	LED 10W P30SN DIM 30KSP	10	75	850	85.0	3000K	80	3.6"	3.8"	8380	15°
LED12P30SD30KSPB	LED 10W P30SN DIM 30KSP BLACK	10	75	850	85.0	3000K	80	3.6"	3.8"	8380	15°
LED12P30SD35KFL	LED 10W P30SN DIM 35KFL	10	75	850	85.0	3500K	80	3.6"	3.8"	2232	40°
LED12P30SD35KFLB	LED 10W P30SN DIM 35KFL BLACK	10	75	850	85.0	3500K	80	3.6"	3.8"	2232	40°
LED12P30SD35KNFL	LED 10W P30SN DIM 35KNFL	10	75	850	85.0	3500K	80	3.6"	3.8"	4402	25°
LED12P30SD35KNFLB	LED 10W P30SN DIM 35KNFL BLACK	10	75	850	85.0	3500K	80	3.6"	3.8"	4402	25°
LED12P30SD35KSP	LED 10W P30SN DIM 35KSP	10	75	850	85.0	3500K	80	3.6"	3.8"	—	15°
LED12P30SD41KFL	LED 10W P30SN DIM 41KFL	10	75	850	85.0	4100K	80	3.6"	3.8"	2247	40°
LED12P30SD41KFLB	LED 10W P30SN DIM 41KFL BLACK	10	75	850	85.0	4100K	80	3.6"	3.8"	2247	40°
LED12P30SD41KNFL	LED 10W P30SN DIM 41KNFL	10	75	850	85.0	4100K	80	3.6"	3.8"	4895	25°
LED12P30SD41KSP	LED 10W P30SN DIM 41KSP	10	75	850	85.0	4100K	80	3.6"	3.8"	8710	15°
LED12P30SD50KFL	LED 10W P30SN DIM 50KFL	10	75	850	85.0	5000K	80	3.6"	3.8"	2454	40°
LED12P30SD50KNFL	LED 10W P30SN DIM 50KNFL	10	75	850	85.0	5000K	80	3.6"	3.8"	5260	25°
LED12P30SD50KSP	LED 10W P30SN DIM 50KSP	10	75	850	85.0	5000K	80	3.6"	3.8"	9292	15°
10.5W P30 Lamps – Dimmable • 25,000 Hours											
LED12P30D24KFL	LED 10.5W P30 DIM 24KFL	10.5	75	800	76.2	2400K	80	4.6"	3.8"	—	40°
LED12P30D24KNFL	LED 10.5W P30 DIM 24KNFL	10.5	75	800	76.2	2400K	80	4.6"	3.8"	—	25°
LED12P30D24KSP	LED 10.5W P30 DIM 24KSP	10.5	75	800	76.2	2400K	80	4.6"	3.8"	—	15°
LED12P30D27KFL	LED 10.5W P30 DIM 27KFL	10.5	75	850	81.0	2700K	80	4.6"	3.8"	2202	40°
LED12P30D27KFLB	LED 10.5W P30 DIM 27KFL BLACK	10.5	75	850	81.0	2700K	80	4.6"	3.8"	2202	40°
LED12P30D27KNFL	LED 10.5W P30 DIM 27KNFL	10.5	75	850	81.0	2700K	80	4.6"	3.8"	5031	25°
LED12P30D27KNFLB	LED 10.5W P30 DIM 27KNFL BLACK	10.5	75	850	81.0	2700K	80	4.6"	3.8"	5031	25°
LED12P30D27KSP	LED 10.5W P30 DIM 27KSP	10.5	75	850	81.0	2700K	80	4.6"	3.8"	9193	15°
LED12P30D27KSPB	LED 10.5W P30 DIM 27KSP BLACK	10.5	75	850	81.0	2700K	80	4.6"	3.8"	9193	15°
LED12P30D30KFL	LED 10.5W P30 DIM 30KFL	10.5	75	850	81.0	3000K	80	4.6"	3.8"	2389	40°
LED12P30D30KFLB	LED 10.5W P30 DIM 30KFL BLACK	10.5	75	850	81.0	3000K	80	4.6"	3.8"	2389	40°
LED12P30D30KNFL	LED 10.5W P30 DIM 30KNFL	10.5	75	850	81.0	3000K	80	4.6"	3.8"	5528	25°
LED12P30D30KNFLB	LED 10.5W P30 DIM 30KNFL BLACK	10.5	75	850	81.0	3000K	80	4.6"	3.8"	5528	25°
LED12P30D30KSP	LED 10.5W P30 DIM 30KSP	10.5	75	850	81.0	3000K	80	4.6"	3.8"	9006	15°
LED12P30D30KSPB	LED 10.5W P30 DIM 30KSP BLACK	10.5	75	850	81.0	3000K	80	4.6"	3.8"	9006	15°
LED12P30D35KFL	LED 10.5W P30 DIM 35KFL	10.5	75	850	81.0	3500K	80	4.6"	3.8"	2362	40°
LED12P30D35KNFL	LED 10.5W P30 DIM 35KNFL	10.5	75	850	81.0	3500K	80	4.6"	3.8"	5029	25°
LED12P30D35KSP	LED 10.5W P30 DIM 35KSP	10.5	75	850	81.0	3500K	80	4.6"	3.8"	9735	15°
LED12P30D41KFL	LED 10.5W P30 DIM 41KFL	10.5	75	850	81.0	4100K	80	4.6"	3.8"	2561	40°
LED12P30D41KFLB	LED 10.5W P30 DIM 41KFL BLACK	10.5	75	850	81.0	4100K	80	4.6"	3.8"	2561	40°
LED12P30D41KNFL	LED 10.5W P30 DIM 41KNFL	10.5	75	850	81.0	4100K	80	4.6"	3.8"	5781	25°
LED12P30D41KNFLB	LED 10.5W P30 DIM 41KNFL BLACK	10.5	75	850	81.0	4100K	80	4.6"	3.8"	5781	25°
LED12P30D41KSP	LED 10.5W P30 DIM 41KSP	10.5	75	850	81.0	4100K	80	4.6"	3.8"	9491	15°
LED12P30D41KSPB	LED 10.5W P30 DIM 41KSP BLACK	10.5	75	850	81.0	4100K	80	4.6"	3.8"	9491	15°
LED12P30D50KFL	LED 10.5W P30 DIM 50KFL	10.5	75	850	81.0	5000K	80	4.6"	3.8"	2437	40°
LED12P30D50KFLB	LED 10.5W P30 DIM 50KFL BLACK	10.5	75	850	81.0	5000K	80	4.6"	3.8"	2437	40°
LED12P30D50KNFL	LED 10.5W P30 DIM 50KNFL	10.5	75	850	81.0	5000K	80	4.6"	3.8"	5575	25°
LED12P30D50KSP	LED 10.5W P30 DIM 50KSP	10.5	75	850	81.0	5000K	80	4.6"	3.8"	9647	15°

NOTE: All items come in shipping cartons of 12.





LED COB PAR Lamps

ITEM #	DESCRIPTION	WATTS	REPLACEMENT WATTS	LUMENS	LPW	COLOR	CRI	MOL (inches)	DIA (inches)	MEASURED CBCP	BEAM ANGLE
13.5W P30 Lamps – Dimmable • 25,000 Hours											
LED14P30D24KFL	LED 13.5W P30 DIM 24KFL	13.5	75	1000	74.1	2400K	80	4.6"	3.8"	–	40°
LED14P30D24KNFL	LED 13.5W P30 DIM 24KNFL	13.5	75	1000	74.1	2400K	80	4.6"	3.8"	–	25°
LED14P30D24KNFLB	LED 13.5W P30 DIM 24KNFL BLACK	13.5	75	1000	74.1	2400K	80	4.6"	3.8"	–	25°
LED14P30D24KSP	LED 13.5W P30 DIM 24KSP	13.5	75	1000	74.1	2400K	80	4.6"	3.8"	–	15°
LED14P30D27KFL	LED 13.5W P30 DIM 27KFL	13.5	75	1050	77.8	2700K	80	4.6"	3.8"	2693	40°
LED14P30D27KFLB	LED 13.5W P30 DIM 27KFL BLACK	13.5	75	1050	77.8	2700K	80	4.6"	3.8"	2693	40°
LED14P30D27KNFL	LED 13.5W P30 DIM 27KNFL	13.5	75	1050	77.8	2700K	80	4.6"	3.8"	5808	25°
LED14P30D27KNFLB	LED 13.5W P30 DIM 27KNFL BLACK	13.5	75	1050	77.8	2700K	80	4.6"	3.8"	5808	25°
LED14P30D27KSP	LED 13.5W P30 DIM 27KSP	13.5	75	1050	77.8	2700K	80	4.6"	3.8"	10563	15°
LED14P30D27KSPB	LED 13.5W P30 DIM 27KSP BLACK	13.5	75	1050	77.8	2700K	80	4.6"	3.8"	10563	15°
LED14P30D30KFL	LED 13.5W P30 DIM 30KFL	13.5	75	1050	77.8	3000K	80	4.6"	3.8"	2849	40°
LED14P30D30KFLB	LED 13.5W P30 DIM 30KFLB	13.5	75	1050	77.8	3000K	80	4.6"	3.8"	2849	40°
LED14P30D30KNFL	LED 13.5W P30 DIM 30KNFL	13.5	75	1050	77.8	3000K	80	4.6"	3.8"	6392	25°
LED14P30D30KNFLB	LED 13.5W P30 DIM 30KNFL BLACK	13.5	75	1050	77.8	3000K	80	4.6"	3.8"	6392	25°
LED14P30D30KSP	LED 13.5W P30 DIM 30KSP	13.5	75	1050	77.8	3000K	80	4.6"	3.8"	11181	15°
LED14P30D30KSPB	LED 13.5W P30 DIM 30KSP BLACK	13.5	75	1050	77.8	3000K	80	4.6"	3.8"	11181	15°
LED14P30D35KFL	LED 13.5W P30 DIM 35KFL	13.5	75	1050	77.8	3500K	80	4.6"	3.8"	–	40°
LED14P30D35KFLB	LED 13.5W P30 DIM 35KFL BLACK	13.5	75	1050	77.8	3500K	80	4.6"	3.8"	–	40°
LED14P30D35KNFL	LED 13.5W P30 DIM 35KNFL	13.5	75	1050	77.8	3500K	80	4.6"	3.8"	–	25°
LED14P30D35KSP	LED 13.5W P30 DIM 35KSP	13.5	75	1050	77.8	3500K	80	4.6"	3.8"	–	15°
LED14P30D41KFL	LED 13.5W P30 DIM 41KFL	13.5	75	1050	77.8	4100K	80	4.6"	3.8"	2661	40°
LED14P30D41KFLB	LED 13.5W P30 DIM 41KFL BLACK	13.5	75	1050	77.8	4100K	80	4.6"	3.8"	2661	40°
LED14P30D41KNFL	LED 13.5W P30 DIM 41KNFL	13.5	75	1050	77.8	4100K	80	4.6"	3.8"	5781	25°
LED14P30D41KNFLB	LED 13.5W P30 DIM 41KNFL BLACK	13.5	75	1050	77.8	4100K	80	4.6"	3.8"	5781	25°
LED14P30D41KSP	LED 13.5W P30 DIM 41KSP	13.5	75	1050	77.8	4100K	80	4.6"	3.8"	12465	15°
LED14P30D41KSPB	LED 13.5W P30 DIM 41KSP BLACK	13.5	75	1050	77.8	4100K	80	4.6"	3.8"	12465	15°
LED14P30D50KFL	LED 13.5W P30 DIM 50KFL	13.5	75	1050	77.8	5000K	80	4.6"	3.8"	2837	40°
LED14P30D50KFLB	LED 13.5W P30 DIM 50KFL BLACK	13.5	75	1050	77.8	5000K	80	4.6"	3.8"	2837	40°
LED14P30D50KNFL	LED 13.5W P30 DIM 50KNFL	13.5	75	1050	77.8	5000K	80	4.6"	3.8"	5875	25°
LED14P30D50KSP	LED 13.5W P30 DIM 50KSP	13.5	75	1050	77.8	5000K	80	4.6"	3.8"	12073	15°
13.5W P38 Lamps – Dimmable • 25,000 Hours											
LED14P38D24KFL	LED 13.5W P38 DIM 24KFL	13.5	90	1000	74.1	2400K	80	5.3"	4.8"	–	40°
LED14P38D24KNFL	LED 13.5W P38 DIM 24KNFL	13.5	90	1000	74.1	2400K	80	5.3"	4.8"	–	25°
LED14P38D24KSP	LED 13.5W P38 DIM 24KSP	13.5	90	1000	74.1	2400K	80	5.3"	4.8"	–	15°
LED14P38D27KFL	LED 13.5W P38 DIM 27KFL	13.5	90	1050	77.8	2700K	80	5.3"	4.8"	2480	40°
LED14P38D27KNFL	LED 13.5W P38 DIM 27KNFL	13.5	90	1050	77.8	2700K	80	5.3"	4.8"	7649	25°
LED14P38D27KNFLB	LED 13.5W P38 DIM 27KNFL BLACK	13.5	90	1050	77.8	2700K	80	5.3"	4.8"	7649	25°
LED14P38D27KSP	LED 13.5W P38 DIM 27KSP	13.5	90	1050	77.8	2700K	80	5.3"	4.8"	12073	15°
LED14P38D27KSPB	LED 13.5W P38 DIM 27KSP BLACK	13.5	90	1050	77.8	2700K	80	5.3"	4.8"	12073	15°
LED14P38D30KFL	LED 13.5W P38 DIM 30KFL	13.5	90	1050	77.8	3000K	80	5.3"	4.8"	2498	40°
LED14P38D30KNFL	LED 13.5W P38 DIM 30KNFL	13.5	90	1050	77.8	3000K	80	5.3"	4.8"	7606	25°
LED14P38D30KSP	LED 13.5W P38 DIM 30KSP	13.5	90	1050	77.8	3000K	80	5.3"	4.8"	11845	15°
LED14P38D30KWFL	LED 13.5W P38 DIM 30KWFL	13.5	90	1050	77.8	3000K	80	5.3"	4.8"	–	60°
LED14P38D35KFL	LED 13.5W P38 DIM 35KFL	13.5	90	1050	77.8	3500K	80	5.3"	4.8"	2736	40°
LED14P38D35KFLB	LED 13.5W P38 DIM 35KFL BLACK	13.5	90	1050	77.8	3500K	80	5.3"	4.8"	2736	40°
LED14P38D35KNFL	LED 13.5W P38 DIM 35KNFL	13.5	90	1050	77.8	3500K	80	5.3"	4.8"	–	25°
LED14P38D35KSP	LED 13.5W P38 DIM 35KSP	13.5	90	1050	77.8	3500K	80	5.3"	4.8"	12856	15°

NOTE: All items come in shipping cartons of 12.





LED COB PAR Lamps

ITEM #	DESCRIPTION	WATTS	REPLACEMENT WATTS	LUMENS	LPW	COLOR	CRI	MOL (inches)	DIA (inches)	MEASURED CBCP	BEAM ANGLE
13.5W P38 Lamps – Dimmable • 25,000 Hours - Continued											
LED14P38D41KFL	LED 13.5W P38 DIM 41KFL	13.5	90	1050	77.8	4100K	80	5.3"	4.8"	2678	40°
LED14P38D41KFLB	LED 13.5W P38 DIM 41KFL BLACK	13.5	90	1050	77.8	4100K	80	5.3"	4.8"	2678	40°
LED14P38D41KNFL	LED 13.5W P38 DIM 41KNFL	13.5	90	1050	77.8	4100K	80	5.3"	4.8"	8310	25°
LED14P38D41KSP	LED 13.5W P38 DIM 41KSP	13.5	90	1050	77.8	4100K	80	5.3"	4.8"	13535	15°
LED14P38D41KSPB	LED 13.5W P38 DIM 41KSP BLACK	13.5	90	1050	77.8	4100K	80	5.3"	4.8"	13535	15°
LED14P38D50KFL	LED 13.5W P38 DIM 50KFL	13.5	90	1050	77.8	5000K	80	5.3"	4.8"	2647	40°
LED14P38D50KFLB	LED 13.5W P38 DIM 50KFL BLACK	13.5	90	1050	77.8	5000K	80	5.3"	4.8"	2647	40°
LED14P38D50KNFL	LED 13.5W P38 DIM 50KNFL	13.5	90	1050	77.8	5000K	80	5.3"	4.8"	8071	25°
LED14P38D50KSP	LED 13.5W P38 DIM 50KSP	13.5	90	1050	77.8	5000K	80	5.3"	4.8"	12418	15°
15W P38 Lamps – Dimmable • 25,000 Hours											
LED17P38D24KFL	LED 15W P38 DIM 24KFL	15	120	1050	70.0	2400K	80	5.3"	4.8"	–	40°
LED17P38D24KNFL	LED 15W P38 DIM 24KNFL	15	120	1050	70.0	2400K	80	5.3"	4.8"	–	25°
LED17P38D24KSP	LED 15W P38 DIM 24KSP	15	120	1050	70.0	2400K	80	5.3"	4.8"	–	15°
LED17P38D27KFL	LED 15W P38 DIM 27KFL	15	120	1200	80.0	2700K	80	5.3"	4.8"	2757	40°
LED17P38D27KFLB	LED 15W P38 DIM 27KFL BLACK	15	120	1200	80.0	2700K	80	5.3"	4.8"	2757	40°
LED17P38D27KNFL	LED 15W P38 DIM 27KNFL	15	120	1200	80.0	2700K	80	5.3"	4.8"	8857	25°
LED17P38D27KSP	LED 15W P38 DIM 27KSP	15	120	1200	80.0	2700K	80	5.3"	4.8"	16239	15°
LED17P38D30KFL	LED 15W P38 DIM 30KFL	15	120	1200	80.0	3000K	80	5.3"	4.8"	3106	40°
LED17P38D30KFLB	LED 15W P38 DIM 30KFL BLACK	15	120	1200	80.0	3000K	80	5.3"	4.8"	3106	40°
LED17P38D30KNFL	LED 15W P38 DIM 30KNFL	15	120	1200	80.0	3000K	80	5.3"	4.8"	9274	25°
LED17P38D30KNFLB	LED 15W P38 DIM 30KNFL BLACK	15	120	1200	80.0	3000K	80	5.3"	4.8"	9274	25°
LED17P38D30KSP	LED 15W P38 DIM 30KSP	15	120	1200	80.0	3000K	80	5.3"	4.8"	18492	15°
LED17P38D30KSPB	LED 15W P38 DIM 30KSP BLACK	15	120	1200	80.0	3000K	80	5.3"	4.8"	18492	15°
LED17P38D30KWFLB	LED 15W P38 DIM 30KWFL BLACK	15	120	1200	80.0	3000K	80	5.3"	4.8"	–	60°
LED17P38D35KFL	LED 15W P38 DIM 35KFL	15	120	1200	80.0	3500K	80	5.3"	4.8"	2994	40°
LED17P38D35KFLB	LED 15W P38 DIM 35KFL BLACK	15	120	1200	80.0	3500K	80	5.3"	4.8"	2994	40°
LED17P38D35KNFL	LED 15W P38 DIM 35KNFL	15	120	1200	80.0	3500K	80	5.3"	4.8"	9405	25°
LED17P38D35KNFLB	LED 15W P38 DIM 35KNFL BLACK	15	120	1200	80.0	3500K	80	5.3"	4.8"	9405	25°
LED17P38D35KSP	LED 15W P38 DIM 35KSP	15	120	1200	80.0	3500K	80	5.3"	4.8"	18094	15°
LED17P38D41KFL	LED 15W P38 DIM 41KFL	15	120	1200	80.0	4100K	80	5.3"	4.8"	2870	40°
LED17P38D41KFLB	LED 15W P38 DIM 41KFL BLACK	15	120	1200	80.0	4100K	80	5.3"	4.8"	2870	40°
LED17P38D41KNFL	LED 15W P38 DIM 41KNFL	15	120	1200	80.0	4100K	80	5.3"	4.8"	9288	25°
LED17P38D41KNFLB	LED 15W P38 DIM 41KNFLB	15	120	1200	80.0	4100K	80	5.3"	4.8"	9288	25°
LED17P38D41KSP	LED 15W P38 DIM 41KSP	15	120	1200	80.0	4100K	80	5.3"	4.8"	18408	15°
LED17P38D41KSPB	LED 15W P38 DIM 41KSP BLACK	15	120	1200	80.0	4100K	80	5.3"	4.8"	18408	15°
LED17P38D50KFL	LED 15W P38 DIM 50KFL	15	120	1200	80.0	5000K	80	5.3"	4.8"	2713	40°
LED17P38D50KFLB	LED 15W P38 DIM 50KFL BLACK	15	120	1200	80.0	5000K	80	5.3"	4.8"	2713	40°
LED17P38D50KNFL	LED 15W P38 DIM 50KNFL	15	120	1200	80.0	5000K	80	5.3"	4.8"	9387	25°
LED17P38D50KSP	LED 15W P38 DIM 50KSP	15	120	1200	80.0	5000K	80	5.3"	4.8"	19721	15°

NOTE: All items come in shipping cartons of 12.





LED COB PAR Lamps

ITEM #	DESCRIPTION	WATTS	REPLACEMENT WATTS	LUMENS	LPW	COLOR	CRI	MOL (inches)	DIA (inches)	MEASURED CBCP	BEAM ANGLE
18.5W P38 High Output Lamps – Dimmable • 25,000 Hours											
LED17HOP38D27KFL	LED 18.5W HOP38 DIM 27KFL	18.5	150	1800	97.3	2700K	80	5.3"	4.8"	—	40°
LED17HOP38D27KNFL	LED 18.5W HOP38 DIM 27KNFL	18.5	150	1800	97.3	2700K	80	5.3"	4.8"	—	25°
LED17HOP38D27KSP	LED 18.5W HOP38 DIM 27KSP	18.5	150	1800	97.3	2700K	80	5.3"	4.8"	—	15°
LED17HOP38D27KSPB	LED 18.5W HOP38 DIM 27KSP BLACK	18.5	150	1800	97.3	2700K	80	5.3"	4.8"	—	15°
LED17HOP38D30KFL	LED 18.5W HOP38 DIM 30KFL	18.5	150	1825	98.6	3000K	80	5.3"	4.8"	2693	40°
LED17HOP38D30KFLB	LED 18.5W HOP38 DIM 30KFL BLACK	18.5	150	1825	98.6	3000K	80	5.3"	4.8"	2693	40°
LED17HOP38D30KNFL	LED 18.5W HOP38 DIM 30KNFL	18.5	150	1825	98.6	3000K	80	5.3"	4.8"	5808	25°
LED17HOP38D30KNFLB	LED 18.5W HOP38 DIM 30KNFL BLACK	18.5	150	1825	98.6	3000K	80	5.3"	4.8"	5808	25°
LED17HOP38D30KSP	LED 18.5W HOP38 DIM 30KSP	18.5	150	1825	98.6	3000K	80	5.3"	4.8"	10563	15°
LED17HOP38D30KSPB	LED 18.5W HOP38 DIM 30KSP BLACK	18.5	150	1825	98.6	3000K	80	5.3"	4.8"	10563	15°
LED17HOP38D35KFL	LED 18.5W HOP38 DIM 35KFL	18.5	150	1850	100.0	3500K	80	5.3"	4.8"	2849	40°
LED17HOP38D35KFLB	LED 18.5W HOP38 DIM 35KFL BLACK	18.5	150	1850	100.0	3500K	80	5.3"	4.8"	2849	40°
LED17HOP38D35KNFL	LED 18.5W HOP38 DIM 35KNFL	18.5	150	1850	100.0	3500K	80	5.3"	4.8"	6392	25°
LED17HOP38D35KSP	LED 18.5W HOP38 DIM 35KSP	18.5	150	1850	100.0	3500K	80	5.3"	4.8"	6392	15°
LED17HOP38D35KWFL	LED 18.5W HOP38 DIM 35KWFL	18.5	150	1850	100.0	3500K	80	5.3"	4.8"	11181	60°
LED17HOP38D41KFL	LED 18.5W HOP38 DIM 41KFL	18.5	150	1900	102.7	4100K	80	5.3"	4.8"	11181	40°
LED17HOP38D41KNFL	LED 18.5W HOP38 DIM 41KNFL	18.5	150	1900	102.7	4100K	80	5.3"	4.8"	—	25°
LED17HOP38D41KSP	LED 18.5W HOP38 DIM 41KSP	18.5	150	1900	102.7	4100K	80	5.3"	4.8"	—	15°
LED17HOP38D50KFL	LED 18.5W HOP38 DIM 50KFL	18.5	150	2000	108.1	5000K	80	5.3"	4.8"	—	40°
LED17HOP38D50KNFL	LED 18.5W HOP38 DIM 50KNFL	18.5	150	2000	108.1	5000K	80	5.3"	4.8"	—	25°
LED17HOP38D50KSP	LED 18.5W HOP38 DIM 50KSP	18.5	150	2000	108.1	5000K	80	5.3"	4.8"	2661	15°

NOTE: All items come in shipping cartons of 12.



TECHNOLOGY CAST IN A BEAUTIFUL LIGHT

For over 20 years, TCP has been designing, developing and delivering energy-efficient lighting into the market. Thanks to our cutting-edge technology and manufacturing expertise, we have shipped billions of high quality lighting products. With TCP, you can count on a lighting product that is designed to meet the needs of the market - that transforms your surroundings and envelopes you in warmth - lighting that generates beauty with every flip of the switch.

Sales:

Date:

Model:

Project:

Rep:

Catalog Number:

Type:

Notes:



For more information on the quality and care TCP can deliver, call us at **800.324.1496** or visit tcp.com

325 Campus Dr. | Aurora, Ohio 44202 | P: 800.324.1496 | F: 877.487.0516